



BEARING DRIVESHAFT ANDERSON, INC.



28 mm x 58 mm x 16 mm NSK 62/28 Ball bearing

Bearing No. 62/28

62/28 Bearing 2D drawings and 3D CAD models

Size	28x58x16 mm
Bore Diameter	28 mm
Outer Diameter	58 mm
Width	16 mm
d	28 mm
D	58 mm
B	16 mm
C	16 mm
r min.	1 mm
da min.	33 mm
da max	35,5 mm
Da max.	53 mm
ra max.	1 mm
Weight	0,175 Kg
Basic dynamic load rating (C)	16,6 kN
Basic static load rating (C0)	9,5 kN
(Grease) Lubrication Speed	12 000 r/min
(Oil) Lubrication Speed	14 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.172
EAN	0029176063770
Product Group	B00308



BEARING DRIVESHAFT ANDERSON, INC.

Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	28MM Bore; 58MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Weight / LBS	0.2624
Outside Diameter	2.283 Inch 58 Millimeter
Bore	1.102 Inch 28 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
SRI	4.41
hidYobi	62/28
LangID	1



BEARING DRIVESHAFT ANDERSON, INC.

D_	58
SREX	0.04
B_	16
da min	33
hidTable	ecat_NSRDGB
Oil rpm	14000
SRE	4.63
mass	0.175
GRS rpm	12000
ra	1
SRIX	0.02
D_a	53
SRIN	0
C0	9.5
fo	13.9
SREN	0
DE_	51.731
Prod_Type3	DGBB_SR_OT
DA_	8.731
bomp	0
Z_	9
yobi	62/28
C_conv	16600
ALPHA_	0
SDM_	43
r	1
KBRG	6101
SBRG	2
DI_	34.269