



# BEARING DRIVESHAFT ANDERSON, INC.

## HSR15C1SS(GK) THK Linear Guide Block Only Standard Grade Interchangeable HSR Series

Bearing No. HSR15C1SS(GK)

Days to Ship	Same Day
RoHS	10
Block Type	[Wide] C: Flanged w/Tapped and Thru Holes
Nominal Part Number	15
Mounting Height M	24 mm
Material	Carbon Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	10900
Basic Load Rating Static Rating Co(N)	15700
Allowable Static Moment MA(N m)	94.5
Allowable Static Moment MB(N m)	94.5
Allowable Static Moment MC(N m)	99.8
Symbols for Dust Resistance	SS: End and Side Seal (Shortest Leadtime)
Block external dimension W	47 mm
Block external dimension L	56.6 mm
Mounting hole for blocks	Tapped and Thru Holes
Mounting Hole Dimension S(M)	M5
Mounting Hole Dimension	4.5

HSR15C1SS(GK) Bearing 2D drawings and 3D CAD models



## BEARING DRIVESHAFT ANDERSON, INC.

H(∅)	
Mounting Hole Screw Depth	Through mm
Block dimension L1	38.8 mm