



# BEARING DRIVESHAFT ANDERSON, INC.

## HSR15C1UU(GK) THK Linear Guide Block Only Standard Grade Interchangeable HSR Series

Bearing No. HSR15C1UU(GK)

Days to Ship	4 Days
RoHS	10
Block Type	[Wide] C: Flanged w/Tapped and Thru Holes
Nominal Part Number	15
Mounting Height M	24 mm
Material	Carbon Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	10900
Basic Load Rating Static Rating Co(N)	15700
Allowable Static Moment MA(N m)	94.5
Allowable Static Moment MB(N m)	94.5
Allowable Static Moment MC(N m)	99.8
Block Mounting Hole Pitch (Width Direction)	38 mm
Block Mounting Hole Pitch (Length Direction)	30 mm
Block Mounting Hole Diameter	4.5
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	4.5

HSR15C1UU(GK) Bearing 2D drawings and 3D CAD models



## BEARING DRIVESHAFT ANDERSON, INC.

Symbols for Dust Resistance	UU: End seal
Block external dimension W	47 mm
Block external dimension L	56.6 mm
Mounting hole for blocks	Tapped and Thru Holes
Mounting Hole Dimension S(M)	M5
Mounting Hole Dimension H( $\varnothing$ )	4.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	38.8 mm