



# BEARING DRIVESHAFT ANDERSON, INC.

## 2SRS5WMUU+110LM THK Miniature Linear Guide Stocked Sizes Standard and Wide Standard Grade SRS Series

Bearing No. 2SRS5WMUU+110LM

2SRS5WMUU+110LM Bearing 2D drawings and 3D CAD models

|  |           |
|--|-----------|
| Days to Ship                                 | 4 Days    |
| The number of LM blocks combined with a axis | 2         |
| Nominal Part Number                          | 5W        |
| Rail Type                                    | Wide Rail |
| Rail Width W1                                | 10 mm     |
| Mounting Height M                            | 6.5 mm    |
| Rail Length L                                | 110 mm    |
| Retainer                                     | Available |
| Rolling Element                              | Ball      |
| Basic Load Rating Dynamic Rating C(N)        | 584       |
| Basic Load Rating Static Rating Co(N)        | 703       |
| Allowable Static Moment MA(N m)              | 1.57      |
| Allowable Static Moment MB(N m)              | 1.83      |
| Allowable Static Moment MC(N m)              | 3.58      |
| Block external dimension W                   | 17 mm     |
| Block external dimension L                   | 22.1 mm   |
| Number of Block Mounting Holes(holes)        | 2         |
| Mounting Hole Dimension S(M)                 | M3        |
|  |           |



## BEARING DRIVESHAFT ANDERSON, INC.

|                              |         |
|------------------------------|---------|
| Mounting Hole Screw<br>Depth | Thru mm |
| Block dimension L1           | 13.7 mm |