



# BEARING DRIVESHAFT ANDERSON, INC.

HSR15B[1,2,3,4,5,6,7,8,9]+[6  
4-3000/1]L[H,P,SP,UP] THK Standard  
Linear Guide Accuracy and Preload Selectable  
HSR Series

Bearing No.  
HSR15B[1,2,3,4,5,6,7,8,9]+[64-3000/1]L[H,P,  
SP,UP]

HSR15B[1,2,3,4,5,6,7,8,9]+[64-300  
0/1]L[H,P,SP,UP] Bearing 2D drawings and 3D  
CAD models

Days to Ship	7 Days
Block Type	[Wide] B: Flanged w/Thru Holes (Obsolete)
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Material	Carbon Steel
Mounting Height M	24 mm
Rail Length L	64 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Retainer	N/A
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	10900
Basic Load Rating Static Rating Co(N)	15700
Allowable Static Moment MA(N m)	94.5
Allowable Static Moment MB(N m)	94.5



## BEARING DRIVESHAFT ANDERSON, INC.

Allowable Static Moment MC(N m)	99.8
Block external dimension W	47 mm
Block external dimension L	56.6 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension H( $\varnothing$ )	4.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	38.8 mm