



# BEARING DRIVESHAFT ANDERSON, INC.

## SSR15XW1M(GK) THK Radial Linear Guide Block Only Interchangeable SSR Series

Bearing No. SSR15XW1M(GK)

SSR15XW1M(GK) Bearing 2D drawings and 3D CAD models

Days to Ship	Quote
RoHS	10
Block Type	[Standard] W: Standard
Nominal Part Number	15
Rail Type	Standard
Mounting Height M	24 mm
Material	Stainless Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	14700
Basic Load Rating Static Rating Co(N)	16500
Allowable Static Moment MA(N m)	79.2
Allowable Static Moment MB(N m)	48.6
Allowable Static Moment MC(N m)	96.2
Block Mounting Hole Pitch (Width Direction)	26 mm
Block Mounting Hole Pitch (Length Direction)	26 mm
Block Mounting Hole Diameter	4
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	4.5



## BEARING DRIVESHAFT ANDERSON, INC.

Symbols for Dust Resistance	No Seals
Block external dimension W	34 mm
Block external dimension L	56.9 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	7 mm
Block dimension L1	39.9 mm