



BEARING DRIVESHAFT ANDERSON, INC.

SR15SB1UUM(GK) THK Radial Linear Guide (Block Only) Interchangeable SR Series

Bearing No. SR15SB1UUM(GK)

SR15SB1UUM(GK) Bearing 2D drawings and 3D CAD models

Days to Ship	Quote
RoHS	10
Block Type	[Wide Short] SB: Short Compact
Nominal Part Number	15
Rail Type	Standard
Mounting Height M	24 mm
Material	Stainless Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5390
Basic Load Rating Static Rating Co(N)	11100
Allowable Static Moment MA(N m)	32.6
Allowable Static Moment MB(N m)	20.3
Allowable Static Moment MC(N m)	65.4
Block Mounting Hole Pitch (Width Direction)	41 mm
Block Mounting Hole Diameter	4.5
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	3.5
Symbols for Dust Resistance	UU: End seals



BEARING DRIVESHAFT ANDERSON, INC.

Block external dimension W	52 mm
Block external dimension L	40.4 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension H(\varnothing)	4.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	22.9 mm