



BEARING DRIVESHAFT ANDERSON, INC.

SR20W1UU(GK) THK Radial Linear Guide (Block Only) Interchangeable SR Series

Bearing No. SR20W1UU(GK)

Days to Ship	4 Days
RoHS	10
Block Type	[Standard] W: Standard
Nominal Part Number	20
Rail Type	Standard
Mounting Height M	28 mm
Material	Carbon Steel
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	12500
Basic Load Rating Static Rating Co(N)	25200
Allowable Static Moment MA(N m)	146
Allowable Static Moment MB(N m)	89.6
Allowable Static Moment MC(N m)	194
Block Mounting Hole Pitch (Width Direction)	32 mm
Block Mounting Hole Pitch (Length Direction)	32 mm
Block Mounting Hole Diameter	5
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	6

SR20W1UU(GK) Bearing 2D drawings and 3D CAD models



BEARING DRIVESHAFT ANDERSON, INC.

Symbols for Dust Resistance	UU: End seals
Block external dimension W	42 mm
Block external dimension L	66.2 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M5
Mounting Hole Screw Depth	8 mm
Block dimension L1	46.7 mm