



# BEARING DRIVESHAFT ANDERSON, INC.

## SRS7WGM+[33-300/1]LM THK Linear Guides Full Ball SRS-G Accuracy and Preload Selectable

Bearing No. SRS7WGM+[33-300/1]LM

Days to Ship	27 Days
Block Type	[Standard] M: Compact
The number of LM blocks combined with a axis	1
Nominal Part Number	7W
Rail Type	Wide Rail
Rail Width W1	14 mm
Mounting Height M	9 mm
Rail Length L	33 ~ 300 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	1630
Basic Load Rating Static Rating Co(N)	2510
Allowable Static Moment MA(N m)	8.87
Allowable Static Moment MB(N m)	10.2
Allowable Static Moment MC(N m)	20.3
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	25 mm
Block external dimension L	31 mm
Number of Block Mounting	4

SRS7WGM+[33-300/1]LM Bearing 2D drawings and 3D CAD models



## BEARING DRIVESHAFT ANDERSON, INC.

Holes(holes)	
Mounting Hole Dimension S(M)	M3
Mounting Hole Screw Depth	2.8 mm
Block dimension L1	20.4 mm