



BEARING DRIVESHAFT ANDERSON, INC.

SSR15XW[1,2,3,4,5,6,7,8,9]C
 1+[64-3000/1]LY THK Linear Guide Caged Ball
 Radial SSR Accuracy and Preload Selectable

Bearing No.
 SSR15XW[1,2,3,4,5,6,7,8,9]C1+[64-3000/1]LY

SSR15XW[1,2,3,4,5,6,7,8,9]C1+[64-3000/1]LY Bearing 2D drawings and 3D CAD models

Days to Ship	3 Days
Block Type	[Standard] W: Standard
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Mounting Height M	24 mm
Material	Carbon Steel
Rail Length L	64 ~ 3000 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	14700
Basic Load Rating Static Rating Co(N)	16500
Allowable Static Moment MA(N m)	79.2
Allowable Static Moment MB(N m)	48.6
Allowable Static Moment MC(N m)	96.2
Block external dimension W	34 mm
Block external dimension L	56.9 mm



BEARING DRIVESHAFT ANDERSON, INC.

Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	7 mm
Block dimension L1	39.9 mm