



# BEARING DRIVESHAFT ANDERSON, INC.

SR15SB[1,2,3,4,5,6,7,8,9]C1  
 M+[47-1240/1]LM THK Radial Load Linear  
 Guide Accuracy and Preload Selectable SR Series

Bearing No.  
 SR15SB[1,2,3,4,5,6,7,8,9]C1M+[47-1240/1]LM

SR15SB[1,2,3,4,5,6,7,8,9]C1M+[47  
 -1240/1]LM Bearing 2D drawings and 3D CAD models

Days to Ship	Quote
Block Type	[Wide Short] SB: Short Compact
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Material	Stainless Steel
Mounting Height M	24 mm
Rail Length L	47 ~ 1240 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5390
Basic Load Rating Static Rating Co(N)	11100
Allowable Static Moment MA(N m)	32.6
Allowable Static Moment MB(N m)	20.3
Allowable Static Moment MC(N m)	65.4
Block Mounting Hole Pitch (Width Direction)	41 mm



## BEARING DRIVESHAFT ANDERSON, INC.

Block Mounting Hole Diameter	4.5
Rail Mounting Hole Pitch	60 mm
Rail Mounting Hole Diameter	3.5
Block external dimension W	52 mm
Block external dimension L	40.4 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension H( $\varnothing$ )	4.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	22.9 mm