



# BEARING DRIVESHAFT ANDERSON, INC.

SR15TB[1,2,3,4,5,6,7,8,9]C1+  
 [64-3000/1]L[H,P,SP,UP] THK Radial  
 Load Linear Guide Accuracy and Preload  
 Selectable SR Series

Bearing No.  
 SR15TB[1,2,3,4,5,6,7,8,9]C1+[64-3000/1]L[H,  
 P,SP,UP]

SR15TB[1,2,3,4,5,6,7,8,9]C1+[64-3  
 000/1]L[H,P,SP,UP] Bearing 2D drawings and  
 3D CAD models

Days to Ship	5 Days
Block Type	[Wide] TB: Flanged w/Thru Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Material	Carbon Steel
Mounting Height M	24 mm
Rail Length L	64 ~ 3000 mm
Radial Clearance	Light Preload
Accuracy Grade	High Grade / Precision Grade / Super Precision Grade / Extra High Precision Grade
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	9510
Basic Load Rating Static Rating Co(N)	19300
Allowable Static Moment MA(N m)	92.5
Allowable Static Moment MB(N m)	56.7
Allowable Static Moment	113



## BEARING DRIVESHAFT ANDERSON, INC.

MC(N m)	
Block external dimension W	52 mm
Block external dimension L	57 mm
Mounting hole for blocks	Thru Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension H( $\varnothing$ )	4.5
Mounting Hole Screw Depth	Through mm
Block dimension L1	39.5 mm