



BEARING DRIVESHAFT ANDERSON, INC.

SR15V[1,2,3,4,5,6,7,8,9][DD,
 KK,LL,RR,SS,UU,ZZ]C1+[47-300
 0/1]L THK Radial Load Linear Guide Accuracy
 and Preload Selectable SR Series

Bearing No.
 SR15V[1,2,3,4,5,6,7,8,9][DD,KK,LL,RR,
 SS,UU,ZZ]C1+[47-3000/1]L

SR15V[1,2,3,4,5,6,7,8,9][DD,KK
 ,LL,RR,SS,UU,ZZ]C1+[47-3000/1]L
 Bearing 2D drawings and 3D CAD models

Days to Ship	5 Days
Block Type	[Short] V: Short
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Material	Carbon Steel
Mounting Height M	24 mm
Rail Length L	47 ~ 3000 mm
Radial Clearance	Light Preload
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5390
Basic Load Rating Static Rating Co(N)	11100
Allowable Static Moment MA(N m)	32.6
Allowable Static Moment MB(N m)	20.3
Allowable Static Moment MC(N m)	65.4
Symbols for Dust Resistance	SS: End and Side Seals /



BEARING DRIVESHAFT ANDERSON, INC.

	UU: End Seals
Advanced Seal Options (Longer Leadtime)	DD: Double End Seals and Side Seals / KK: DD + Metal Scraper / LL: Low Resistance End Seal / RR: Low Resistance End + Side Seal / ZZ: SS + Metal Scraper
Block external dimension W	34 mm
Block external dimension L	40.4 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	2
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	7 mm
Block dimension L1	22.9 mm