



BEARING DRIVESHAFT ANDERSON, INC.

SR15W[1,2,3,4,5,6,7,8,9][DD
 ,KK,LL,RR,SS,UU]+[64-3000/1]L
 THK Radial Load Linear Guide Accuracy and
 Preload Selectable SR Series

Bearing No.
 SR15W[1,2,3,4,5,6,7,8,9][DD,KK,LL,RR,
 SS,UU]+[64-3000/1]L

SR15W[1,2,3,4,5,6,7,8,9][DD,K
 K,LL,RR,SS,UU]+[64-3000/1]L Bearing 2D
 drawings and 3D CAD models

Days to Ship	5 Days
Block Type	[Standard] W: Standard
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	15
Rail Width W1	15 mm
Material	Carbon Steel
Mounting Height M	24 mm
Rail Length L	64 ~ 3000 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	9510
Basic Load Rating Static Rating Co(N)	19300
Allowable Static Moment MA(N m)	92.5
Allowable Static Moment MB(N m)	56.7
Allowable Static Moment MC(N m)	113
Symbols for Dust Resistance	SS: End and Side Seals /



BEARING DRIVESHAFT ANDERSON, INC.

	UU: End Seals
Advanced Seal Options (Longer Leadtime)	DD: Double End Seals and Side Seals / KK: DD + Metal Scraper / LL: Low Resistance End Seal / RR: Low Resistance End + Side Seal
Block external dimension W	34 mm
Block external dimension L	57 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	4
Mounting Hole Dimension S(M)	M4
Mounting Hole Screw Depth	7 mm
Block dimension L1	39.5 mm