



BEARING DRIVESHAFT ANDERSON, INC.

HRW17CA[1,2,3,4,5,6,7,8,9]
M+[64-800/1]LM THK Linear Guide Wide Rail
HRW Accuracy and Preload Selectable

Bearing No.
HRW17CA[1,2,3,4,5,6,7,8,9]M+[64-800/1]LM

HRW17CA[1,2,3,4,5,6,7,8,9]M+[6
4-800/1]LM Bearing 2D drawings and 3D CAD models

Days to Ship	Quote
Block Type	[Wide] CA: Flanged w/Tapped Holes and Middle Holes
The number of LM blocks combined with a axis	1 ~ 9
Nominal Part Number	17
Rail Width W1	33 mm
Material	Stainless Steel
Mounting Height M	17 mm
Rail Length L	64 ~ 800 mm
Radial Clearance	Normal
Accuracy Grade	Normal Grade (Best Leadtime)
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	5530
Basic Load Rating Static Rating Co(N)	9100
Allowable Static Moment MA(N m)	46.4
Allowable Static Moment MB(N m)	46.4
Allowable Static Moment MC(N m)	144
Block Mounting Hole Pitch	53 mm



BEARING DRIVESHAFT ANDERSON, INC.

(Width Direction)	
Block Mounting Hole Pitch (Length Direction)	26 mm
Block Mounting Hole Diameter	3.3
Rail Mounting Hole Pitch	40 mm
Rail Mounting Hole Diameter	4.5
Symbols for Dust Resistance	None (Not Recommended)
Block external dimension W	60 mm
Block external dimension L	50.8 mm
Mounting hole for blocks	Tapped and Thru Holes
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension S(M)	M4
Mounting Hole Dimension H(\varnothing)	3.3
Mounting Hole Screw Depth	Through mm
Block dimension L1	33.6 mm