



BEARING DRIVESHAFT ANDERSON, INC.

SHW35CR1UU(GK) THK Caged Ball Wide Rail Linear Guide (Block Only) Interchangeable SHW Series

Bearing No. SHW35CR1UU(GK)

Days to Ship	4 Days
RoHS	10
Block Type	[Standard] CR: Compact
Nominal Part Number	35
Rail Type	Wide Rail
Mounting Height M	35 mm
Radial Clearance	Normal
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	35500
Basic Load Rating Static Rating Co(N)	49200
Allowable Static Moment MA(N m)	603
Allowable Static Moment MB(N m)	603
Allowable Static Moment MC(N m)	1630
Block Mounting Hole Pitch (Width Direction)	76 mm
Block Mounting Hole Pitch (Length Direction)	50 mm
Block Mounting Hole Diameter	8
Rail Mounting Hole Pitch	80 mm
Rail Mounting Hole Diameter	7

SHW35CR1UU(GK) Bearing 2D drawings and 3D CAD models



BEARING DRIVESHAFT ANDERSON, INC.

Symbols for Dust Resistance	UU: End seal
Grease Nipple Option	None
Block external dimension W	62 mm
Block external dimension L	72.8 mm
Mounting hole for blocks	Tapped Holes
Number of Block Mounting Holes(holes)	6
Mounting Hole Dimension S(M)	M6
Mounting Hole Screw Depth	6 mm
Block dimension L1	56.6 mm