



BEARING DRIVESHAFT ANDERSON, INC.

GSR30T[1,2,3,4,5,6,7,8,9]+[8
2-2004/1]LHR THK Linear Guide Rail with Rack
Gear Model GSR-R

Bearing No.
GSR30T[1,2,3,4,5,6,7,8,9]+[82-2004/1]LHR

GSR30T[1,2,3,4,5,6,7,8,9]+[82-200
4/1]LHR Bearing 2D drawings and 3D CAD models

| | |
|------------------------------------------|--------------|
| Days to Ship | Quote |
| Block Type | Standard |
| Rail Width W1 | 50.55 mm |
| Mounting Height M | 33 mm |
| Number of blocks | 1 ~ 9 |
| Rail Length L | 82 ~ 2004 mm |
| Accuracy Grade | High Grade |
| Callout Size | 30 |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 18800 |
| Basic Load Rating Static Rating Co(N) | 25900 |
| Allowable static moment MA(N · m) | 282 |
| Allowable static moment MB(N · m) | 243 |
| The outside dimension W of block | 57 mm |
| The outside dimension L of block | 103 mm |
| Mounting Hole Dimension S(M) | M8 |
| Mounting Hole Screw Depth | 12 mm |
| The dimension L1 of bocks | 70.3 mm |



BEARING DRIVESHAFT ANDERSON, INC.