



BEARING DRIVESHAFT ANDERSON, INC.

HR2042T+[112-2200/1]L[H,P,SP,UP][F(AP-C),F(AP-CF),F(AP-HC)] THK
Separated Linear Guide Side Rails Set Model HR

Bearing No. HR2042T+[112-2200/1]L[H,P,SP,UP][F(AP-C),F(AP-CF),F(AP-HC)]

HR2042T+[112-2200/1]L[H,P,SP,UP][F(AP-C),F(AP-CF),F(AP-HC)] Bearing 2D drawings and 3D CAD models

| | |
|---------------------------------------|--|
| Days to Ship | 42 Days |
| Rail Width W1 | 15.6 mm |
| Mounting Height M | 20 mm |
| Number of blocks | 1 |
| Material | Carbon Steel |
| Rail Length L | 112 ~ 2200 mm |
| Accuracy Grade | High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade |
| Callout Size | 2042 |
| Rolling Element | Ball |
| Basic Load Rating Dynamic Rating C(N) | 13600 |
| Basic Load Rating Static Rating Co(N) | 22900 |
| Allowable static moment MA(N · m) | 530 |
| Allowable static moment MB(N · m) | 530 |
| The outside dimension W of block | 26.3 mm |
| The outside dimension L of block | 110.7 mm |
| Mounting Hole Dimension S(M) | M6 |
| | |



BEARING DRIVESHAFT ANDERSON, INC.

| | |
|---|---|
| The dimension L1 of bocks | 75.7 mm |
| LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.) | Not Provided |
| LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.) | Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - Special Fluororesin Coating / Industrial Hard Chrome Plating |